
LONDECK SIERRA features a unique crevassed texture and comes in six earthy tones. It is part of Lonseal's Londeck series of resilient exterior sheet vinyl with slightly embossed surfaces that withstand high volumes of pedestrian traffic and weather-wear. Because of its versatility, Londeck has been utilized in spaces such as pools, hotel and condo decks, and stairways.

STANDARD SIZES (nominal)

Overall thickness: 0.080" (2.0 mm)

Wear layer thickness: 0.031" (0.8 mm)

Roll size: 6' (1.83 m) wide x 60' (18.3 m)

Weight: 0.7 lbs./sq ft., 245 lbs./roll

Colors: Six available

15-YEAR WARRANTY

Lonseal offers a 15-year limited warranty.

TECHNICAL DATA

Weatherometer ASTM D1499	No crazing, cracking, spalling, or softening
Accelerated Aging, ASTM D756	43 psi
Tensile and Elongation (≤55%), ASTM D751	Weathered: 9%; Aged: 20%
Bond Strength (10psi. Min.), ASTM C297	Control: 30 psi; Aged: 43 psi; Freeze-Thaw: 22 psi
Abrasion (max 0.020"), ASTM D1242	0.001"
Percolation (0.5" Max), AC 39	0.1"
Water Absorption (15% Max), ASTM D570	5%
Chemical Resistance, ASTM D2299	No crazing, softening, delamination, or spalling
Freeze Thaw (15% Max), ASTM C67	1%
Concentrated Load, AC39	No damage noted
Wind Uplift, FM 1-52	No cracking, spalling, tearing, delamination, or failures of fasteners