

Lonseal's LONDECK series features resilient exterior sheet vinyl with slightly embossed surfaces that withstand high volumes of pedestrian traffic and weather-wear. Because of its versatility, Londeck has been utilized in spaces such as pools, hotel and condo decks, and stairways. Though specifically designed for exterior spaces, the Londeck line is equally appropriate for interiors.

## STANDARD SIZES (nominal)

**Overall thickness:** 0.080" (2.0 mm)

**Wear layer thickness:** 0.031" (0.8 mm)

**Roll size:** 6' (1.83 m) wide x 60' (18.3 m)

**Weight:** 0.63 lbs./sq. ft., 225 lbs./roll/

**Colors:** Eight available

## 15-YEAR WARRANTY

Lonseal offers a 15-year limited warranty.

## TECHNICAL DATA

<b>Weatherometer, ASTM D1499</b> .....	No crazing, cracking, spalling, or softening
<b>Accelerated Aging, ASTM D756</b> .....	43 psi
<b>Tensile and Elongation (≤55%), ASTM D751</b> .....	Weathered: 9%; Aged: 20%
<b>Bond Strength (10psi. Min.), ASTM C297</b> .....	Control: 30 psi; Aged: 43 psi; Freeze-Thaw: 22 psi
<b>Abrasion (max 0.020"), ASTM D1242</b> .....	0.001"
<b>Percolation (0.5" Max), AC 39</b> .....	0.1"
<b>Water Absorption (15% Max), ASTM D570</b> .....	5%
<b>Chemical Resistance, ASTM D2299</b> .....	No crazing, softening, delamination, or spalling
<b>Freeze Thaw (15% Max), ASTM C67</b> .....	1%
<b>Concentrated Load, AC39</b> .....	No damage noted
<b>Wind Uplift, FM 1-52</b> .....	No cracking, spalling, tearing, delamination, or failures of fasteners