

LONWOVEN Topseal

FEATURES (data shown is nominal):

Roll Width: 6 ft. (1.8 m)

Roll Length: 60 ft. (18.3 m)

Overall Thickness: 0.080 in. (2.0 mm)

Wear Layer Thickness: 0.020 in. (0.5 mm)

Weight: 0.6 lbs./sq. ft. (3.1 kg/m²)

TOPSEAL: Factory-applied urethane finish

PHthalate FREE: REACH Compliant, SVHC free

MEETS FMVSS 302: CFR 49 §571.302 Flammability of Interior Materials

ASTM F1303 CLASSIFICATION: Type I, Grade 1, Class B, Commercial Use

CERTIFIED: FloorScore®

EXCLUSIVE LONSEAL® FORMULATIONS: [Topseal](#), GreenAir® & [GreenMedic®](#)

LEEDv4/4.1 CONTRIBUTION Building & Construction Interiors:

Environmental Product Declarations Option 1

Sourcing of Raw Materials Option 2

Low-Emitting Materials

SUGGESTED APPLICATIONS:

Healthcare & Assisted Living

Corporate & Education

Retail & Hospitality

Displays & Fixtures

Exhibits & Entertainment

Marine

Specialty Vehicles

WARNING: California Proposition 65

SPECIFICATIONS:

Pattern	LINEN,CROSS-HATCH
Finish	SMOOTH
Width	6 ft. (72 in.) (1.8 m)
Specs	ANTIMICROBIAL, FLOORSCORE, LOW VOC, CONTRIBUTES TO LEED V4/4.1, ASTM F1303 CLASSIFIED, FMVSS 302, TOPSEAL, REACH, PHTHALATE FREE, SVHC FREE