

MATERIAL SAFETY DATA SHEET

SECTION I – PRODUCT AND COMPANY INFORMATION

DATE: September 2008

Product Name:

Flame Stop I, I-C, I-DS, II, III and IV

Hazard Rating:

Health: 1 Fire: 0 Reactivity: 0 PPI:

Company Identification:

Flame Stop, Inc.
924 Blue Mound Rd.
Fort Worth, TX 76131

Telephone:

1-877-397-7867

Chemtrec (24 hr):

1-800-424-9300

Product Class:

Proprietary

Shipping Name:

One of the following:
Flame Stop I, I-C, I-DS, II, III, IV

SECTION II – INGREDIENT AND HAZARD INFORMATION

PROPRIETARY NON HAZARDOUS CHEMICALS

SECTION III – PHYSICAL DATA

Form:

liquid

Appearance/color:

clear, Flame Stop II is white

pH Value:

6.5 - 7.5

Boiling Range:

212F

Evaporation Rate:

Slower than n-Butyl Acetate

Vapor Density:

Heavier than air

% Volatile Weight:

N/A

% Volatile / Volume:

N/A

Specific Gravity:

proprietary

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flammability Class:

IIIB

Flash Point:

N/A

Extinguishing Media: Carbon Dioxide, Foam, Dry Chemical, water

Special Firefighting Procedures: Use self contained breathing apparatus

Unusual Fire and Explosion Hazards: none

SECTION V – HEALTH HAZARD DATA

Effects of Over Exposure:

Eye irritation, nausea. Prolonged exposure may cause drying of the skin.

Permissible Exposure Level: Undetermined

First Aid:

INHALATION: Remove from exposure area

EYE CONTACT: Flush with water for 15 minutes

SKIN CONTACT: Wash with soap and water

POSSIBLE ROUTES OF ENTRY: Inhalation, ingestion, skin absorption

SECTION VI – STABILITY AND REACTIVITY

Stability: Yes

Hazardous Polymerization: Will not occur

Incompatibility: Avoid water-reactive agents.

Hazardous decomposition Products: Carbon Monoxide, Carbon Dioxide

SECTION VII – SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:

Remove spills with inert absorbent.

Waste Disposal Method:

Dispose of in accordance with Federal, State and Local regulations.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

RESPIRATORY PROTECTION: If in direct contact or spray application use a dust or paint mask.

VENTILATION: Required only when applying in a confined area

EYE PROTECTION: Wear safety glasses or goggles to guard against splashes.

PROTECTIVE GLOVES: Not required unless direct contact

DISCLAIMER: The data herein is believed to be correct. However, since conditions of use are outside our control it does not represent a warranty or representation for which Flame Stop, Inc. assumes any legal responsibility. Flame Stop makes no guarantee or warranty since they have no control over application conditions.